

1 _____ BILL NO. _____

2 INTRODUCED BY _____
3 (Primary Sponsor)

4 BY REQUEST OF THE ATTORNEY GENERAL

5
6 A BILL FOR AN ACT ENTITLED: "AN ACT REMOVING THE EXEMPTION FROM MUDFLAPS FOR MOTOR
7 VEHICLES NOT ORIGINALLY EQUIPPED WITH MUDFLAPS OR MOTOR VEHICLES FOR WHICH MUDFLAPS
8 WERE NOT REQUIRED AT THE TIME OF MANUFACTURE; AND AMENDING SECTION 61-9-407, MCA."

9
10 BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:

11

12 **Section 1.** Section 61-9-407, MCA, is amended to read:

13 **"61-9-407. Fenders, splash aprons, or flaps required on certain vehicles -- dimension and location.**

14 (1) A person may not move, or permit to be moved, a vehicle, except a motorcycle, quadricycle,
15 motor-driven cycle, or farm tractor, as defined in this title, upon the public highways without having first
16 equipped the rearmost wheels or set of wheels of the vehicle with fenders, splash aprons, or flaps. The
17 fenders, splash aprons, or flaps must be designed, constructed, and attached to the vehicle in a manner
18 that arrests and deflects dirt, mud, water, rocks, and other substances that may be picked up by the rear
19 wheels of the vehicle and thrown into the air, as follows:

20 (a) If the vehicle is equipped with fenders, the fenders must extend in full width from a point
21 above and forward of the center of the tire or tires over and to the rear of the tires.

22 (b) If the vehicle is equipped with splash aprons or flaps, the splash aprons or flaps must extend
23 downward in full width from a point not lower than halfway between the center of the tire or tires and the
24 top of the tire or tires and to the rear of the tires.

25 (c) If the vehicle is in excess of 8,000 pounds gross vehicle weight or rating, the fenders, splash
26 aprons, or flaps must extend downward to a point that is not more than 10 inches above the surface of
27 the highway when the vehicle is empty.

28 (d) If the vehicle is 8,000 pounds or less gross vehicle weight or rating, the fenders, splash
29 aprons, or flaps must extend downward to a point that is not more than 20 inches above the surface of
30 the highway when the vehicle is empty.



1 (2) Fenders, splash aprons, or flaps, as used in subsection (1), must be constructed as follows:

2 (a) when measured on the cross-sections of the tread of the wheel or on the combined
3 cross-sections of the treads of multiple wheels, the fender, splash apron, or flap extends at least to each
4 side of the width of the tire or of the combined width of the multiple tires; and

5 (b) the fender, splash apron, or flap is capable at all times of arresting and deflecting dirt, mud,
6 water, or other substance that may be picked up and carried by the wheel or wheels.

7 (3) This section does not apply to street rod vehicles; ~~motor vehicles not originally equipped with~~
8 ~~fenders, splash aprons, or flaps; or motor vehicles for which fenders, splash aprons, or flaps were not~~
9 ~~required by federal law or regulation at the time of manufacture.~~

10 (4) For purposes of 61-9-430 and this section, "street rod" means a vehicle manufactured before
11 1949 that has been modified in body style or design."

12 - END -