1	SENATE BILL NO. 352
2	INTRODUCED BY J. BOHLINGER
3	
4	A BILL FOR AN ACT ENTITLED: "AN ACT REQUIRING THAT ALL VEHICLES REQUIRED TO BE EQUIPPED
5	WITH HEADLAMPS HAVE THE HEADLAMPS OR DRIVING LAMPS ILLUMINATED AT ALL TIMES WHILE
6	THE VEHICLE IS BEING OPERATED ON A HIGHWAY; AND AMENDING SECTIONS 61-8-312, 61-9-201,
7	61-9-202, 61-9-203, 61-9-207, 61-9-213, 61-9-215, 61-9-216, 61-9-221, AND 61-9-225, MCA."
8	
9	BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:
10	
11	Section 1. Section 61-8-312, MCA, is amended to read:
12	"61-8-312. Special speed limitations on trucks, truck tractors, and motor-driven cycles. (1) Except
13	as provided in 61-8-303, 61-8-309, 61-8-310, and subsection (2) of this section, the speed limit for a truck or
14	truck tractor of more than 1 ton "manufacturer's rated capacity" traveling on:
15	(a) completed sections of interstate is 65 miles an hour; and
16	(b) four-lane divided highways and completed sections of primary and secondary highways is 60 miles
17	an hour during the daytime and 55 miles an hour during the nighttime as those terms are defined in 61-8-303.
18	(2) Except as provided in 61-8-303, 61-8-309, and 61-8-310, the speed limit for a vehicle subject to a
19	term permit under 61-10-124(2)(d) or a truck-trailer-trailer or truck tractor-semitrailer-trailer-trailer combination
20	of vehicles subject to special permits under 61-10-124(4) is 55 miles an hour unless otherwise stated in the
21	permit.
22	(3) A person may not operate a motor-driven cycle at any time mentioned in 61-9-201(2) at a speed
23	greater than 35 miles an hour unless the motor-driven cycle is equipped with a headlamp or lamps that are
24	adequate to reveal a person or vehicle at a distance of 300 feet ahead."
25	
26	Section 2. Section 61-9-201, MCA, is amended to read:
27	"61-9-201. When lighted lamps are required. Every (1) A driver of a vehicle that is required to be
28	equipped with headlamps upon a highway within this state shall drive with the headlamps or driving lamps
29	lighted at all times that the vehicle is being operated on a highway.
30	(2) at <u>At</u> any time from one-half hour after before sunset to one-half hour before after sunrise and at any



SB0352.01

other time when due to because of insufficient light or unfavorable atmospheric conditions persons and vehicles
on the highway are not clearly discernible at a distance of 500 feet ahead, drivers of all vehicles shall display
lighted lamps and illuminating devices as hereinafter respectively required for different classes of vehicles,
subject to exceptions with respect to parked vehicles."

5

6

Section 3. Section 61-9-202, MCA, is amended to read:

7 "61-9-202. Visibility distance and mounted height of lamps. (1) Whenever requirement is
 8 hereinafter declared as to Requirements in this part that specify the distance from which certain lamps and
 9 devices shall must render objects visible or within which such the lamps or devices shall must be visible, said
 10 provisions shall apply during the times stated in 61-9-201 in respect pertain to a vehicle without <u>a</u> load when
 11 operated upon a straight, level, unlighted highway under normal atmospheric conditions during the times stated
 12 in 61-9-201(2) unless a different time or condition is expressly stated.

(2) Whenever requirement is hereinafter declared as to <u>Requirements in this part that specify</u> the
 mounted height of lamps or devices it shall mean pertain to the distance from the center of such the lamp or
 device to the level ground upon which the vehicle stands when such the vehicle is without a load."

16

17

Section 4. Section 61-9-203, MCA, is amended to read:

"61-9-203. Headlamps on motor vehicles. (1) A motor vehicle, other than a motorcycle, quadricycle,
or motor-driven cycle, or other vehicle not required under this chapter to be equipped with headlamps, must be
equipped with at least two headlamps, with at least one on each side of the front of the motor vehicle, that
comply with the requirements and limitations set forth in this chapter.

22 (2) A motorcycle, quadricycle, or motor-driven cycle must be equipped with at least one and not more 23 than two headlamps that comply with the requirements and limitations of this chapter. If a motorcycle is 24 registered under 61-3-411 as a collector's item, it need not be equipped with headlamps: however, 25 if it the motorcycle is not equipped with headlamps, it may not be operated upon a highway or street from 26 one-half hour after before sunset to one-half hour before after sunrise or if persons and vehicles are not clearly 27 discernible at a distance of 500 feet. A motorcycle may be equipped with a means of modulating the high beam 28 of its headlamps between high and low beam at a rate of 200 to 280 flashes a minute;. however However, an 29 operator may not modulate the headlamps at that rate during periods when headlamps are required to be lighted 30 by the period specified in 61-9-201(2).



SB0352.01

- (3) A headlamp upon a motor vehicle, including a motorcycle, quadricycle, and motor-driven cycle, must
 be located at a height, measured from the center of the headlamp, of not more than 54 inches or less than 22
 inches, to be measured as provided in 61-9-202(2).
- 4 (4) When headlamps are required to be lighted by 61-9-201, a <u>A</u> person may not operate a motor
 5 vehicle on a highway with headlamps that are composed of, covered by, or treated with a tinted or colored
 6 material, substance, system, or component that obscures the headlamps or diminishes the distance of visibility
 7 required by this section.
- 8 (5) This section does not prohibit the operation or sale of a motor vehicle the headlamps of which are 9 composed of, covered by, or treated with a tinted or colored material, substance, system, or component with 10 which the vehicle was sold or could have been equipped for sale when new as standard or optional equipment 11 in compliance with federal statute or regulation governing the sale at the time of manufacture."
- 12

13

Section 5. Section 61-9-207, MCA, is amended to read:

14 "61-9-207. Application of succeeding sections. (1) Sections 61-9-208 through 61-9-223 and 61-9-225
15 through 61-9-229 apply as stated in those sections to vehicles of the type enumerated in those sections when
16 operated upon a highway. The vehicles must be equipped as required, and <u>subject to subsection (2) of this</u>
17 section, all lamp lighting equipment required must be lighted at all times mentioned in 61-9-201(2), except that
18 clearance and side marker lamps need not be lighted on a vehicle when operated within a municipality when
19 there is sufficient light to render clearly discernible persons and vehicles on the highway at a distance of 1,000
20 feet.

(2) Vehicles that are required to be equipped with headlamps are subject to the requirement that the
 headlamps or driving lamps be lighted at all times that the vehicle is being operated on a highway, as provided
 in 61-9-201."

- 20 <u>III</u>
- 24

25 Section 6. Section 61-9-213, MCA, is amended to read:

26 "61-9-213. Lamp or flag on projecting load. (1) Whenever When the load upon a vehicle extends to
27 the rear 4 feet or more beyond the rear of the vehicle, the following lamps and reflectors must be displayed at
28 the extreme rear end of the load, at the times specified in 61-9-201(2):

(a) a red lamp plainly visible from a distance of at least 500 feet to the sides and 1,000 feet to the rear
 and located to indicate maximum overhang; and

- 3 -



(b) a red reflector visible at night at all distances from 100 feet to 600 feet to the rear when directly in
 front of lawful lower beams of headlamps.

3 (2) The red lights and reflectors required under this section must be in addition to the red lights required 4 upon a vehicle. At any other time, there must be displayed at the extreme rear end of the load a red flag or cloth 5 not less than 12 inches square, marking the extremities of the load, at each point where a lamp or reflector would 6 otherwise be required by this section."

- 7
- 8

Section 7. Section 61-9-215, MCA, is amended to read:

9 "61-9-215. Lamps on farm tractors, farm equipment, and implements of husbandry. (1) A farm 10 tractor and a self-propelled farm equipment unit or implement of husbandry not equipped with an electric lighting 11 system must at all times mentioned in 61-9-201(2) be equipped with at least one lamp displaying a white light 12 visible from a distance of not less than 500 feet to the front of the vehicle, at least one lamp displaying a red light 13 visible from a distance of not less than 500 feet to the rear of the vehicle, and two red reflectors visible from a 14 distance of 100 to 600 feet to the rear when illuminated by the upper beams of headlamps. The lights required 15 in this section must be positioned so that one lamp showing to the front and one lamp or reflector showing to 16 the rear indicates indicate the farthest projection of the tractor, unit, or implement on the side of the road used 17 in passing the vehicle.

(2) A combination of farm tractor and towed unit of farm equipment or implement of husbandry not
 equipped with an electric lighting system or an implement of husbandry being towed by a motor vehicle must
 at all times mentioned in 61-9-201(2) be equipped with the following lamps:

(a) at least one lamp mounted to indicate the extreme left projection of the combination and displaying
a white light visible from a distance of not less than 500 feet to the front of the combination; and

(b) two lamps each displaying a red light visible from a distance of not less than 500 feet to the rear of
the combination, or at least one lamp displaying a red light visible from a distance of not less than 500 feet to
the rear of the combination and two red reflectors visible from a distance of 100 to 600 feet to the rear of the
combination when illuminated by the upper beams of headlamps. The lamps or reflectors must be mounted to
indicate the extreme left and right rear projections of the towed unit or implement on the highway.

(3) A farm tractor and a self-propelled unit of farm equipment or implement of husbandry equipped with
 an electric lighting system must at all times mentioned in 61-9-201(2) be equipped with two multiple-beam or
 single-beam headlamps meeting that meet the requirements of 61-9-220 or 61-9-222 and two red lamps visible



from a distance of not less than 500 feet to the rear, or one red lamp visible from a distance of not less than 500 feet to the rear and two red reflectors visible from a distance of 100 to 600 feet to the rear when illuminated by the upper beams of headlamps. The red lamps or reflectors must be mounted in the rear of the farm tractor or self-propelled implement of husbandry to indicate the extreme left and right projections of the vehicle on the highway.

6 (4) A combination of farm tractor and towed farm equipment or towed implement of husbandry equipped
7 with an electric lighting system must at all times mentioned in 61-9-201(2) be equipped with the following lamps:

8 (a) The farm tractor element of the combination must be equipped with two single-beam or
9 multiple-beam headlamps meeting that meet the requirements of 61-9-220 or 61-9-222.

10 (b) The towed unit of farm equipment or implement of husbandry element of the combination must be 11 equipped with two red lamps visible from a distance of not less than 500 feet to the rear or one red lamp visible 12 from a distance of not less than 500 feet to the rear and two red reflectors visible from a distance of 100 to 600 13 feet to the rear when illuminated by the upper beams of headlamps. The red lamps or reflectors must be located 14 to indicate the extreme left and right projections of the towed unit or implement on the highway.

(c) The combination must also be equipped with a lamp displaying a white or amber light, or a shade of color between white and amber, visible from a distance of not less than 500 feet to the front and a lamp displaying a red light visible from a distance of not less than 500 feet to the rear. The lamp or lamps must indicate to the front and rear the farthest projection of the combination on the side of the road used by other vehicles in passing the combination."

20

21

Section 8. Section 61-9-216, MCA, is amended to read:

22 "61-9-216. Lamps on other vehicles and equipment. A vehicle, including animal-drawn vehicles and 23 vehicles referred to in 61-9-109(4), not specifically required by the provisions of this chapter to be equipped with 24 lamps or other lighting devices, must at all times specified in 61-9-201(2) be equipped with at least one lamp 25 displaying a white light visible from a distance of not less than 1,000 feet to the front of the vehicle, and with two 26 lamps displaying red light visible from a distance of not less than 1,000 feet to the rear of the vehicle. The vehicle 27 may have one lamp displaying a red light visible from a distance of not less than 1,000 feet to the rear and two 28 red reflectors visible for distances of 100 to 600 feet to the rear when illuminated by the upper beams of 29 headlamps."

30

Legislative Division

SB0352.01

1 Section 9. Section 61-9-221, MCA, is amended to read: 2 "61-9-221. Use of multiple-beam road-lighting lighting equipment. Whenever When a motor vehicle 3 is being operated on a roadway or shoulder adjacent to a roadway during the times specified in 61-9-201(2), the 4 driver shall use a distribution of light, or composite beam, capable of revealing persons and vehicles at a safe 5 distance in advance of the vehicle, subject to the following requirements and limitations: 6 (1) Whenever When the driver of a vehicle approaches an oncoming vehicle within 1,000 feet, the driver 7 shall use a distribution of light or composite beam that does not project into the eyes of the oncoming driver. The 8 lowermost distribution of light specified in 61-9-220(2) must avoid glare at all times, regardless of road contour 9 and loading. 10 (2) Whenever When the driver of a vehicle follows another vehicle within 500 feet to the rear, the driver 11 shall use a distribution of light permissible under this chapter other than the uppermost distribution of light specified in 61-9-220(1)." 12 13 14 Section 10. Section 61-9-225, MCA, is amended to read: 15 "61-9-225. Number of driving lamps required or permitted. (1) At all times specified in 61-9-201, at 16 least two lighted lamps shall be displayed, one on each side at the front of every motor vehicle other than a 17 motorcycle, quadricycle, or motor-driven cycle, except when such vehicle is parked, subject to the regulations 18 governing lights on parked vehicles. 19 (2) Whenever When a motor vehicle equipped with headlamps as herein required in 61-9-203 is also equipped with any auxiliary lamps or a spot lamp or any other lamp on the front thereof of the vehicle projecting 20 21 a beam of intensity greater than 300 candlepower, not more than a total of no more than four of any such those 22 lamps on the front of a vehicle shall may be lighted at any one time when the vehicle is being operated upon on 23 a highway." 24 - END -



- 6 -